



# ALUSTAVA

TECHNICAL DATA	
Safe working load max.	: 600 kg
Max. permitted wind speed	: 12.5 m/s
Typical GVW	: 32 ton
min. operating weight	: 31.4 ton
Outrigger width and length c/c	
- normal jacking	: 8.0/6.5 m
- one side jacking	: 5.6.2/6.5 m
- narrow jacking	: 3.2/6.5 m
Calculation code	:

EU

PRELIMINARY

All rights reserved  
 This specification may be revised without notice.  
 This document, which is our exclusive intellectual property, shall be treated as strictly private and confidential and shall neither be copied nor communicated to any third person without our written consent.  
 BRONTO SKYLIFT OY AB  
 Tampere Finland

ULOTTUVUUSKAAVIO  
 RÄCKVIDDSDIAGRAM  
 OUTREACH DIAGRAM  
 ARBEITSDIAGRAM  
 DIAGRAMA DE TRABAJO  
 РАБОЧАЯ СХЕМА

SYSTEM Vertex G4	Massa kg Suunnittelija Hyväksyjä	Las RKe	Pun 2016-10-18	Yleistoleranssit Koneistus : SFS4011 Keski Meisto : SFS4012 Levy- ja Hitsustyöt: BBS 2.51
Mittakaava 1 : 225	Arkkikoko A2	Status		



Nimitys  
 Ulottumakaavio  
 S 70 XR, Levitettävä työkori

Piirustus nro.  
**R020152H**  
 Rev.

Rev.	Muutosno.	Muutos	Pvm	Muut.